



REV.	DESCRIPTION	DATE
△	加工適用温度	2013/4/19
△	適用電流更正	2013/5/8

- Material:**
- 1.Housing: Thermoplastic, UL94V-0.
 - 2.Shell: Copper alloy, Nickel-plated.
 - 3.Terminal: Copper alloy, Gold / Tin plated.

- Electrical:**
- 1.Current rating: 1.8 Amp. △
 - 2.Voltage: 30V AC
 - 3.Current resistance: 30mΩ Max.
 - 4.Insulation resistance: 1000MΩ Min.
 - 5.Withstanding voltage: 500V AC.
 - 6.Temperature: -40°C To 85°C △

Ordering Info:
USB-A-R-A-XX

- 1: AU GFU"
- 3: AU 30U"
- B: Black
- W: White

<p>TOLERANCE</p> <p>X ±0.20</p> <p>XX ±0.15</p> <p>XXX ±0.10</p>		<p>DRAWER</p> <p>Drawn <i>Glenn Siao</i></p> <p>CHECK <i>Mhi-Jung Siao</i></p> <p>DESIGNED <i>Glenn Siao</i></p> <p>APPROVAL <i>Steve Tseng Siao</i></p>		<p>NAME</p> <p>USB A Type Female Dip Conn. 90°</p>	
<p>UNITS : mm</p>		<p>DATE 06/01/2010</p>		<p>PART NO. USB-A-R-A-XX</p>	
<p>SCALE 3:1</p>		<p>SIZE A4</p>		<p>DRAW NO. USB-A-R-A</p>	
<p>RECOMMENDED PCB LAYOUT</p>		<p>DATE 06/01/2010</p>		<p>SHEET 1 OF 1</p>	
<p>2-φ2.30</p> <p>2.00</p> <p>7.00</p> <p>13.14</p> <p>4-φ0.92</p> <p>2.71</p>		<p>DESIGNED <i>Glenn Siao</i></p>		<p>REV.</p>	
<p>6.00</p>		<p>APPROVAL <i>Steve Tseng Siao</i></p>		<p>REV.</p>	
<p>6.00</p>		<p>DATE 06/01/2010</p>		<p>REV.</p>	
<p>6.00</p>		<p>DATE 06/01/2010</p>		<p>REV.</p>	
<p>6.00</p>		<p>DATE 06/01/2010</p>		<p>REV.</p>	

SynLight 日亮電子科技有限公司
Sun-Light Electronic Technologies Inc.